



FAQ (English)

<p>My SQuape X is leaking or has got some drops between the tank and base.</p>	<p>Cotton must be placed in front of the liquid holes and the channels. Use the supplied hex wrench to place the cotton into the right position. For liquids with lower VG percentage use a little more cotton and push it a bit more to the liquid holes and channels. Do not press, but to make sure it sits well. It is extremely important that no cotton is on the deck ledge. Use a good amount of cotton to fill the deck. For example, it helps to place cotton in the middle of the deck to build a bridge between the two coils. We recommend to change the cotton periodically. Certain cotton varieties can collapse and then no longer store the liquid sufficiently.</p>
<p>I get dry hits</p>	<p>The cotton was probably pressed too firmly to the liquid holes and the channels within the deck. Either loosen the cotton slightly or lay new cotton.</p>
<p>The wire is cut when assembling</p>	<p>Soft wires, like Ni200 or NiFe and thin wires <0.3mm could be cut by excessive tightening. Place the wire in the hole (centrally) and tighten gently with the hex wrench in the grub screw. Insert the hex wrench with the long side so you apply less force.</p>
<p>No contact to the mod, „no atomizer »</p>	<p>Unscrew the centerpin a little. If this does not help, contact support@squape.ch .</p>
<p>How to clean the SQuape X</p>	<p>There is a need from time to time to unscrew the centerpin and wipe it with a cloth. Condensed water can work its way down to the centerpin despite the sealing protection. We recommend to clean the SQuape X with running water or in an ultrasonic bath. Never clean in a dishwasher.</p>
<p>The TopCap can not be closed properly</p>	<p>Remove the tank from the base, use a 4mm hex wrench, insert from below into the chimney and tighten it. Then the TopCap will close all the way.</p>

The tank can not be put on the base.	Remove the closing ring (see picture in the manual) with a tweezer or paper clip and set it on your deck (see added flyer).
What size of coil do you recommend?	We recommend an inner diameter of 2.5mm for the coils placed on the side. If you like to place a coil in the middle you can build 3 - 4mm coils.
Loose or hard to turn AFC ring	Replace the o-ring with an o-ring from the replacement set. O-rings do have tolerances.
My glass is broken	You've got a spare glass included to your set.
How to get a SQuape X?	Shop list: www.squape.ch or directly at shop.squape.ch
Where do I get more infos and tips?	At www.squape.ch and Facebookgroup: https://www.facebook.com/groups/squape.x.dream/

